

SOLUNA

POWER DESIGNED FOR NIGHT AND DAY

SOLUNA

POWER DESIGNED FOR NIGHT AND DAY



SOLUNA

www.soluna.co | Email: sales@solunabattery.com | Tel.: +86-21-57475835

SOLUNA

www.soluna.co | Email: sales@solunabattery.com | Tel.: +86-21-57475835

Soluna BES 5K Pack is a low-voltage battery solution ideal for Residential and energy storage applications.

The model is adopting by latest **LiFePO₄** technology with intelligent BMS integrated inbuilt blackout protection for energy security, offering a **5kWh** capacity that can be installed in parallel with up to 160 batteries enabling 800kWh of total storage.

With a **10-year** warranty and up to 6000 long cycle life, the BES 5K Pack is a flexible, reliable, high-performance battery storage solution.

Low Voltage



Scalable to 800kWh

Safest LiFePO₄ battery



Long lifespan

Easy Installation



Floor, Wall Mountable



TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Height (mm)	580
Width (mm)	420
Depth (mm)	155
Weight (kg)	48
Installation	Floor-stand, Wall-mounted

ELECTRICAL CHARACTERISTICS

Battery type	Lithium LFP
Nominal capacity (kWh)	5.12
Nominal voltage (V)	51.2
Voltage range (usable) (V)	48-57.6
Max. charge/discharge current (A)	75
Depth of discharge (DoD) (%)	90
Internal resistance (mΩ)	≤60
Cycle life	≥ 6000
Battery pack round-trip efficiency (%)	>95
DC disconnect	MOSFET Fuse

BMS

Power consumption	<3 W (work) <100 mW (sleep)
Monitoring parameters	System voltage System current Cell voltage Cell temperature
Communication	CAN Wi-Fi, RS 485

OPERATING CONDITIONS

Operating temperature (°C)	-10 to 50
Operating temperature (recommended) (°C)	15 to 30
Storage temperature (recommended) (°C)	-30 to 60
Humidity conditions (%)	5 to 95
Altitude (m)	Max. 2,000
Cooling strategy	Natural convection

RELIABILITY AND CERTIFICATION

Hazardous materials classification	Class 9
Transportation	UN38.3
Certification	
Ingress protection rating	IP 54
System configuration	1 to 160 parallel

WARRANTY

Product and performance	10-year warranty
-------------------------	------------------