

# SOLUNA

POWER DESIGNED FOR NIGHT AND DAY

# SOLUNA

POWER DESIGNED FOR NIGHT AND DAY



SOLUNA™

[www.soluna.co](http://www.soluna.co) Email: [sales@solunabattery.com](mailto:sales@solunabattery.com) Tel: +86-21-57475835

SOLUNA™

[www.soluna.co](http://www.soluna.co) Email: [sales@solunabattery.com](mailto:sales@solunabattery.com) Tel: +86-21-57475835

**Soluna Jupiter 32K Pack LV** is a battery solution ideal for residential and small commercial energy storage applications.

The model is adopted by the latest LiFePO<sub>4</sub> technology with an intelligent BMS integrated in the fault protection for energy security, offering a capacity of 32kWh which can be installed in parallel up to 30 batteries allowing 960kWh of total storage.

With a 10-year warranty and 8000 cycle life, the Soluna Jupiter 32K Pack LV is a flexible, reliable and high performance battery storage solution.

IP65



Scalable to 960 kWh

Safest LiFePO<sub>4</sub> battery



Long lifespan

Easy Installation



Floor, Wall mounted



## TECHNICAL SPECIFICATIONS

### PHYSICAL CHARACTERISTICS

Height (mm)	1125
Width (mm)	665
Depth (mm)	220
Weight (kg)	260
Installation	Indoor / Outdoor

### ELECTRICAL CHARACTERISTICS

Battery type	LFP
Total Energy Capacity (kWh)	32.153
Usable Energy Capacity (kWh)	25.722
Nominal capacity (Ah)	628
Nominal voltage (V)	51.2
Voltage range (usable) (V)	44.8 to 56.8
Charge/Discharge Current (A)	290
Charge/Discharge Power (KW)	15
Max.Charge/Discharge Current (A)	290
Max.Charge/Discharge Power (KW)	15
Recommend Depth of Discharge (%)	80
Max Depth of Discharge (%)	90
Cycle life@ 25°C(under standard charge and discharge conditions)	≥8000
DC Disconnect	Contactor / Fuse

### BMS

Monitoring parameters	System voltage System current Cell voltage Cell temperature SOC SOH
Communication	CAN

### OPERATING CONDITIONS

Operating temperature (°C)	-10 to 50
Operating temperature(recommended) (°C)	15 to 30
Storage temperature (recommended)(°C)	-20 to 60
Humidity conditions(%)	5 to 95
Altitude(m)	Max. 2,000
Cooling strategy	Natural convection

### RELIABILITY AND CERTIFICATION

Certification	TBD
Transportation	UN38.3
Ingress protection rating	IP 65

### WARRANTY

Product and performance	10-year standard warranty
-------------------------	---------------------------