SOLUNA

SOLUNA

POWER DESIGNED FOR NIGHT AND DAY





POWER DESIGNED FOR NIGHT AND DAY



POWER DESIGNED FOR NIGHT AND DAY

Soluna 10K Pack LV is a battery solution ideal for residential and small commercial energy storage applications.

The model is adopted by the latest LiFePO4 technology with an intelligent BMS integrated in the fault protection for energy security, offering a capacity of 10kWh which can be installed in parallel up to 30 batteries allowing 300kWh of total storage.

With a 10-year warranty and 10000 cycle life, the Soluna 10K Pack LV is a flexible, reliableand high performance battery storage solution.

IP65





Scalable to 300 kWh

Safest LiFePO₄ battery





Long lifespan

Easy Installation





Floor, Wall mounted



TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Height (mm)	760
Width (mm)	500
Depth (mm)	215
Weight (kg)	100
Installation	Indoor / Outdoor

ELECTRICAL CHARACTERISTICS

Battery type	LFP
Nominal Energy(kWh)	10.24
Usable Energy (kwh)[1]	9.2
Nominal capacity (Ah)	200
Nominal voltage (V)	51.2
Voltage range (usable) (V)	48 to 57.6
Max. charge/ discharge current(A)	100 / 200
Recommended Depth of Discharge (%)	80
Max. Depth of Discharge(%)	90
Internal resistance (mΩ)	≤60
Cycle life@ 25°C(under standard charge and discharge conditions)	≥10000
Pattery pack round trip officionary (9/)	> OF

Battery pack round-trip efficiency (%) >95 DC disconnect Con

Contactor / fuse

BMS

Power consumption	<3W (working)
	<100 mW (sleeping)
Monitoring parameters	System voltage
3.	System current
	Cell voltage

Cell voltage Cell temperature

(

OPERATING CONDITIONS

Communication

Operating temperature (°C)	-10 to 50
Operating temperature(recommended) (°C)	15 to 30
Storage temperature (recommended)(°C)	15 to 30
Humidity conditions(%)	5 to 95
Altitude(m)	Max. 2,000
Cooling strategy	Natural convection

RELIABILITY AND CERTIFICATION

Certification	UL1642
	UN38.3.UL1973.UL9540A
	IECC2C10 CE DOLIC

Transportation UN38.3
Ingress protection rating IP 65

WARRANTY

System configuration

Product and performance 10-year standard warranty

1 to 30 parallel