

# SOLUNA

POWER DESIGNED FOR NIGHT AND DAY

# SOLUNA

POWER DESIGNED FOR NIGHT AND DAY



SOLUNA

www.soluna.co Email: sales@solunabattery.com Tel: +86-21-57475835

SOLUNA

www.soluna.co Email: sales@solunabattery.com Tel: +86-21-57475835

**Soluna Venus 16K-20 Pack LV** is a battery solution ideal for residential and small commercial energy storage applications.

The model is adopted by the latest LiFePO<sub>4</sub> technology with an intelligent BMS integrated in the fault protection for energy security, offering a capacity of 16kWh which can be installed in parallel up to 30 batteries allowing 480kWh of total storage.

With a 10-year warranty and 8000 cycle life, the Soluna Venus 16K-20 Pack LV is a flexible, reliable and high performance battery storage solution.

Easy Installation



Scalable to 480 kWh

Safest LiFePO<sub>4</sub> battery



Long lifespan

Floor Mount  
Wall Mount



## TECHNICAL SPECIFICATIONS

### PHYSICAL CHARACTERISTICS

Height (mm)	850
Width (mm)	545
Depth (mm)	220
Weight (kg)	127
Installation	Floor Mount / Wall Mount

### ELECTRICAL CHARACTERISTICS

Battery type	LFP
Total Energy Capacity (kWh)	16.07
Usable Energy Capacity (kWh)	12.85
Nominal capacity (Ah)	314
Nominal voltage (V)	51.2
Voltage range (usable) (V)	44.8 to 56.8
Charge/Discharge Current (A)	150
Charge/Discharge Power (KW)	7.68
Max.Charge/Discharge Current (A)	160/220
Max.Charge/Discharge Power (KW)	8.2/11.2
Recommend Depth of Discharge (%)	80
Max Depth of Discharge (%)	90
Cycle life@ 25°C(under standard charge and discharge conditions)	≥8000
DC Disconnect	Contactor / Fuse

### BMS

Monitoring parameters	System voltage System current Cell voltage Cell temperature SOC SOH
Communication	CAN

### OPERATING CONDITIONS

Operating temperature (°C)	-10 to 50
Operating temperature(recommended) (°C)	15 to 30
Storage temperature (recommended)(°C)	-20 to 60
Humidity conditions(%)	5 to 95
Altitude(m)	Max. 2,000
Cooling strategy	Natural convection

### RELIABILITY AND CERTIFICATION

Certification	TBD
Transportation	UN38.3
Ingress protection rating	IP 20

### WARRANTY

Product and performance	10-year standard warranty
-------------------------	---------------------------