

# SOLUNA

POWER DESIGNED FOR NIGHT AND DAY

## Venus 16K Pack LV



# TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS	
Dimensions (W*D*H)(mm)	545*220*850
Weight (kg)	127
Installation	Indoor / Outdoor
ELECTRICAL CHARACTERISTICS	
Battery type	LFP
Total Energy Capacity (kWh)	16.07
Usable Energy Capacity (kWh)	14.46
Nominal capacity(Ah)	314
Nominal voltage (V)	51.2
Voltage range (usable) (V)	44.8 to 56.8
Charge/Discharge Current(A)	150
Charge/Discharge Power(KW)	7.68
Max.Charge/Discharge Current(A)	160 / 220
Max.Charge/Discharge Power(KW)	8.2 / 11.2
Recommend Depth of Discharge	80%
Max Depth of Discharge	90%
Cycle life@ 25°C (under standard charge and discharge conditions)	≥8000
DC Disconnect	Contactor / Fuse
BMS	
Monitoring parameters	System voltage . System current . Cell voltage . Cell temperature . SOC . SOH
Communication	CAN
OPERATING CONDITIONS	
Operating temperature (°C)	-10 to 50
Operating temperature(recommended)(°C)	15 to 30
Storage temperature(recommended)(°C)	-20 to 60
Humidity conditions	5 to 95%
Altitude(m)	Max.2,000
Cooling strategy	Natural convection
RELIABILITY AND CERTIFICATION	
Certification	UL1973 . 9540A . 9540 . IEC62619, EMC, ROHS
Transportation	UN38.3
Ingress protection rating	IP65
WARRANTY	
Product and performance	10-year warranty

# KEY FEATURES



IP65



Scalable to 480kWh



Safest LiFePo4 battery



Long lifespan



Easy Installation



Floor, Wall Mounted

The Soluna Venus 16K Pack LV is a residential and small-commercial LiFePO4 battery equipped with an intelligent BMS for enhanced fault protection. Delivering **16 kWh** per unit and scalable up to **480 kWh** with **30 parallel batteries**, it offers secure, flexible, and high-performance energy storage supported by a 10-year warranty and **8,000-cycle lifespan**.

